



999.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Fanless !
- 1GB RAM !
- 1.2 Ghz !



**Support:** [HDD-Installation \[DE\]](#) | [HDD-Installation \[EN\]](#) | [Drivers \(Win\)](#) | [Graphics Driver \(Win\)](#)

Fanless PC-Barebone. For a full-featured PC you only need to add one 2.5" PATA harddrive.

Because of its size (170 x 123 x 56 mm !) the system is perfect for these applications :

- POS
- Digital Signage
- Kiosk

Or use as attractive office-computer or server.

|                |                                                |
|----------------|------------------------------------------------|
| CPU            | VIA Eden Esther 1.2GHz processor               |
| BIOS           | AMI BIOS                                       |
| System Chipset | VIA CX700M                                     |
| I/O Chip       | VT1211                                         |
| System Memory  | Onboard 1024MB DDR2                            |
| MIO            | 1xEIDE(UltraDMA 133),1x PS/2 K/B,1x P/S2 Mouse |
| PRT            | 1x Printer port                                |
| RS232          | 2x RS-232 port                                 |
| USB            | 2 X USB 2.0 Ports (one at front)               |
| Output         | VGA                                            |

|                                     |                                                                                         |
|-------------------------------------|-----------------------------------------------------------------------------------------|
| Display Chipset                     | Integrated VIA UniChrome Pro II,2D/3D Graphics with MPEG4 and WMV9 decoding accelerator |
| Display Memory                      | Up to 128MB share system memory                                                         |
| Display Resolution                  | Up to 1920 x 1440                                                                       |
| Audio AC97 2.2(Codec)               | VIA Vinyl VT1708                                                                        |
| Audio Interface                     | Line Out, Mic In                                                                        |
| Ethernet Chipset                    | Realtek RTL8100B 10/100 Base-T Ethernet                                                 |
| Ethernet Remote Boot ROM            | built-in boot ROM function (PXE Supported)                                              |
| 2.5" Hard Disk installation support | YES                                                                                     |
| Power Requirement                   | +5V@4A                                                                                  |
| Operating Temp                      | 0 ~ 60°C ( 32-140 °F)                                                                   |
| Operating Humidity                  | 0% - 90% relative humidity, non-condensing                                              |
| Size (W x H x D)                    | 170 x 123 x 56 mm                                                                       |
| Weight                              | 970g                                                                                    |
| Certification                       | CE,FCC                                                                                  |